LCFB SERIES RESIDENTIAL LIGHTING



LCFB-1L-MCT5


SINGLE LED PENDANT LIGHT





LCFB created surface mount, rod suspension and wire suspension mount applicaitons. Feature Driver on Board (DOB) technology, with no driver or transformer needed. Fabric lens make the light smooth, perfect for residential and commercial light.

Customer Name: Project Name: Note: Type:



Features

- Multi CCT (Selectable Switch on the LED Board under the lens)
- Brushed Nickel Finish

- 5-Year Warranty
- Glass lens

Technical Specifications

Electrical:

Voltage: 120V AC 50/60Hz

Wattage: 12WPower Factor: >0.90Efficacy: 68 LPW

Mechanical:

- Brush Nickel Finish
- Spun Steel Housing
- Polycarbonate Lens
- Glass Material: 5/64" (2mm) thickness, Ultra Clear Glass
- Power Cord is 40" Long
- Maximum Ambient Temperature: -22°F to 104°F
- IP20 indoor only

Lighting:

- Dimming: TRIAC Dimming (Dimmable Down to 5% Compatible with Traic and ELV Dimmers)
- Total Lumens: 810LM
- Color Temperatures: 2700K/3000K/3500K/4000K/5000K
- Multi CCT (Selectable Switch on back of the fixture)
- Color Rendering Index: CRI ≥ 90
- Beam Angle: 120°
 Rated life: 50.000 Hrs

Applications:

 LCFA created surface mount, rod suspension and wire suspension mount applications. Feature Driver on Board (DOB) technology, with no driver or transformer needed. Fabric lens make the light smooth, perfect for residential and commercial light.

Other Models:

36W | 2430LM | LCFB-3LR-MCT5
 36W | 2430LM | LCFB-3LS-MCT5











Photometrics: LCFB-1L-MCT5





1fc 0.5fc 15 Area 35'x 35' Mounting Height: 9'

BUG Rating: B1-U1-G0

Other Views:







Top View

Performance Table: LCFB-1L-MCT5

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
LCFB-1L-MCT5	12W	120V	810LM	2700K/ 3000K/ 3500K/ 4000K/ 5000K	B1-U1-G0	68

Sample Ordering

Model Color Temp. Light LCFB MCT5 1L

Example:

1. LCFB-1L-MCT5

(FOR LCFB 12W MCT5 FIXTURE 120V)

Other Model: LCFB-3LR-MCT5







Front View



Top View



