

# LHB



LHB-50

LHB-PC-12"  
(Polycarbonate reflector)






LHB-100  
LHB-150

LHB-PC-16"  
(Polycarbonate reflector)



LHB-220

LHB-AL-18"  
(Aluminum)



## TECHNICAL SPECIFICATIONS:

- ⌘ Die-cast aluminum housing with ribbed polycarbonate reflector (aluminum for 220W)
- ⌘ LED: Philips LUMILEDS
- ⌘ Voltage: 120~277V; 60Hz AC
- ⌘ CRI: 80
- ⌘ Power Factor: 95%
- ⌘ L70 design life (50,000 hours)
- ⌘ Operating Temp: -4°F to 122°F
- ⌘ Suitable for Damp Locations
- ⌘ Dimmable in meanwell drivers 150W and 220W

## APPLICATIONS:

⌘ Ideal for general warehouse lighting, loading docks, storage areas, supermarkets. The polycarbonate lens provide 360° illumination combined with crisp, directional, bright 5000K light that will make merchandise clearly visible and eye-catching.



B24

LED HIGH BAYS

## LED HIGH BAYS

CATALOG NO.	WATTS	LUMENS	COLOR TEMP	REPLACEMENT RANGE	DIMENSIONS
LHB-50-CW	50W	6080LM	5000K	100~175 MH	12" (Dia) x 12" (H)
LHB-50-NW	50W	5900LM	4000K	100~175 MH	
LHB-100-CW	100W	10800LM	5000K	250~320 MH	16" (Dia) x 16" (H)
LHB-100-NW	100W	11800LM	4000K	250~320 MH	
LHB-150-CW	150W	15400LM	5000K	340~400 MH	
LHB-150-NW	150W	17000LM	4000K	340~400 MH	16" (Dia) x 10" (H)
LHB-220-CW	220W	24000LM	5000K	350~400 MH	
LHB-220-NW	220W	24000LM	4000K	350~400 MH	

- LHB-BRKT-50      Optional surface mount bracket for 50W
- LHB-BRKT-100      Optional surface mount bracket for 100W
- LHB-BRKT-150      Optional surface mount bracket for 150W

