

DIMENSIONS:

49-2/8" (L) x 3" (H) x 4-1/2" (w)



LLVT2-4FT-40W-50k-D
LLVT2-4FT-40W-40k-D

LED LINEAR VAPOR LIGHT

Ideal for workshops, garages, canopies, parking garages, cold storage facilities, food processing facilities, farmyards, and other harsh, humid, dusty and wet environment lighting applications.

ELECTRICAL SPECIFICATIONS:

- Voltage: 120-277VAC 50/60Hz
- Wattage: 40W
- Power factor: >0.95
- Efficacy: 120LM/W

HOUSING SPECIFICATIONS:

- Polycarbonate construction is highly impact resistant
- Stainless Steel Mounting Brackets Incorporated on the Back
- UV-stabilized Polycarbonate diffuser eliminates glare
- Diffuser crystals enhance even light distribution
- Stainless Steel clips evenly seal the luminaire
- Operating temperature: -22°F~104°F
- Lifespan: 50000 Hrs.
- IP rating: IP66, Suitable for Wet Locations

CERTIFICATIONS: DLC



MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP
LLVT2-4FT-40W-50k-D	40W	120~277V AC	4800LM	5000K
LLVT2-4FT-40W-40k-D	40W	120~277V AC	4800LM	4000K

LIGHTING SPECIFICATIONS:

- Dimming: 0~10V dimmable
- Lens: Opal polycarbonate
- Driver: Quantum
- Total lumens: 4800LM
- Color temperature: 4000K/5000K
- Color rendering index: >82

WARRANTY: 5 years

