


# RSL & SSL



## TECHNICAL SPECIFICATIONS:

- :: Die-cast aluminum with white powder coat finish
- :: Pot light housing is not required even for insulated ceilings
- :: Optics: White translucent acrylic lens
- :: Lens: 0.125" white translucent acrylic
- :: Type IC rated - Approved for direct contact with insulation
- :: CRI: >80
- :: Working voltage: 120V AC
- :: Beam Spread: 100-110°
- :: Dimmable
- :: LED: Seoul DOB (Driver On Board) Technology
- :: Power factor: 90% +
- :: Air-tight and damp location approved
- :: Maximum Ambient Temperature: -40°F~104°F
- :: 5000 Hours, 5-year warranty
- :: ETL-listed
- :: Energy Star-rated



4" & 6" Rough-in plates

## LED ULTRA SLIM RECESSED LIGHTS

CATALOG NO.		WATTS	COLOR TEMP	LUMENS	DIAMETER
ROUND	SQUARE				
RSL4-27K	SSL4-27K	9W	2700K	540LM	4"
RSL4-30K	SSL4-30K	9W	3000K	540LM	
RSL4-40K	SSL4-40K	9W	4000K	540LM	
RSL4-50K	SSL4-50K	9W	5000K	540LM	
RSL6-27K	SSL6-27K	15W	2700K	900LM	6"
RSL6-30K	SSL6-30K	15W	3000K	900LM	
RSL6-40K	SSL6-40K	15W	4000K	900LM	
RSL6-50K	SSL6-50K	15W	5000K	900LM	
RSL4-RI			4" Rough-in Plate		
RSL6-RI			6" Rough-in Plate		

