



- SL-28W-50K-BZ-D
- SL-28W-30K-BZ-D
- SL-28W-50K-WHT-D
- SL-28W-30K-WHT-D

**LED SECURITY LIGHTS**

Ideal for doorway, pathway and alleys. Great for use with optional motion sensors or photocell.

**ELECTRICAL SPECIFICATIONS:**

- Voltage: 120VAC, 50/60Hz
- Wattage: 28W
- Power Factor: 0.90~0.97
- Efficacy: 121LM/W

**HOUSING SPECIFICATIONS:**

- Housing: Die-cast aluminum with powder coat finish
- Mounts flush on wall or 4" round weatherproof box
- Can be installed with any standard LED dimmers (TRIAC types)
- Operating Temperature: -40°F~104°F
- IP Rating: IP65, Suitable for wet locations

**CERTIFICATIONS: ETL**



MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP
SL-28W-50K-BZ-D	28W	120VAC	3400LM	5000K
SL-28W-30K-BZ-D	28W	120VAC	3400LM	3000K
SL-28W-50K-WHT-D	28W	120VAC	3400LM	5000K
SL-28W-30K-WHT-D	28W	120VAC	3400LM	3000K

**OPTIONAL MOTION SENSERN & PHOTOCCELL:**



SL-PIR-WH SL-PIR-BZ SL-HPIR-WH SL-HPIR-BZ SL-PC

MODEL	DESCRIPTION
SL-PIR-WH	120V AC, 180°, 200W Max Load, OUTDOOR MOTION SENSOR (WHITE)
SL-PIR-BZ	120V AC, 180°, 200W Max Load, OUTDOOR MOTION SENSOR (BRONZE)
SL-HPIR-WH	120V AC, 240°, 500W Max Load, OUTDOOR MOTION SENSOR (WHITE)
SL-HPIR-BZ	120V AC, 240°, 500W Max Load, OUTDOOR MOTION SENSOR (BRONZE)
SL-PC	120V AC, Optional Photocell Component for the above series security lights, Incl. WH & BR trims to match security light color

**LIGHTING SPECIFICATIONS:**

- Dimming: Dimmable
- Cover Type: clear lens
- Total lumens: 3400LM
- Color temperature: 5000K/3000K
- Color rendering index: 80
- Light Beam Angle: 120°

**WARRANTY: 7 years**

